



LEISTUNGSINDEX				18	20	22	24	26	
MODUL				ARUM180LTE5	ARUM200LTE5	ARUM220LTE5	ARUM240LTE5	ARUM260LTE5	
Anzahl Innengeräte ¹	Max			29 (45)	32 (50)	35 (56)	39 (61)	42 (64)	
Möglicher Leistungsindex ²	Min - Max			50% - 200%	50% - 200%	50% - 200%	50% - 200%	50% - 200%	
Nennkühlleistung ³			kW	50,4	56,0	61,6	67,2	72,8	
Nennheizleistung ³			kW	50,4	56,0	61,6	67,2	67,2	
Heizleistung	-7°C AT		kW	56,7	63,0	69,3	74,3	74,3	
Heizleistung	-15°C AT		kW	50,4	56,0	61,6	66,0	66,0	
Heizleistung	-20°C AT		kW	45,0	49,5	54,4	58,1	58,4	
Heizleistung	-25°C AT		kW	36,4	38,6	42,4	44,4	45,5	
SEER				8,23	8,05	7,51	7,88	7,55	
SCOP				4,00	3,98	3,90	4,34	4,34	
Leistungsaufnahme ⁴	Kühlen	Nennleistung	kW	10,9	12,8	15,7	17,4	20,2	
	Heizen	Nennleistung	kW	10,1	12,2	14,2	15,9	16,0	
	Max		kW	11,9	14,7	16,8	18,8	19,2	
Betriebsstrom	Kühlen	Nennleistung	A	17,8	20,9	25,6	28,4	33,0	
	Heizen	Nennleistung	A	19,0	24,0	27,4	30,7	30,6	
Einsatzgrenze Außentemperatur	Kühlen		°C	-15 / 48	-15 / 48	-15 / 48	-15 / 48	-15 / 48	
	Heizen		°C	-25 / 18	-25 / 18	-25 / 18	-25 / 18	-25 / 18	
Luftvolumenstrom				19.200	19.200	19.200	19.200	19.200	
Schalldruckpegel ⁵	Kühlen	Max	dB(A)	61,0	62,0	64,5	65,0	65,0	
	Heizen	Max	dB(A)	62,0	64,5	65,5	67,0	67,0	
Schallleistungspegel ⁶	Kühlen	Max	dB(A)	92	93	93	95	95	
	Heizen	Max	dB(A)	95	96	97	99	99	
Externe Statische Pressung		Max	Pa	80	80	80	80	80	
Abmessungen	H x B x T		mm	1.690 x 1.240 x 760	1.690 x 1.240 x 760	1.690 x 1.240 x 760	1.690 x 1.240 x 760	1.690 x 1.240 x 760	
Gewicht			kg	300,0	300,0	300,0	310,0	310,0	
MONTAGE				ARUM180LTE5	ARUM200LTE5	ARUM220LTE5	ARUM240LTE5	ARUM260LTE5	
Rohrleitungsanschlüsse ⁷	2-Leiter	Flüssig	mm (Zoll)	15,88 (5/8)	15,88 (5/8)	15,88 (5/8)	15,88 (5/8)	19,05 (3/4)	
		Saugas	mm (Zoll)	28,58 (1 1/8)	28,58 (1 1/8)	28,58 (1 1/8)	34,9 (1-3/8)	34,9 (1-3/8)	
Rohrleitungsanschlüsse ⁷	3-Leiter	Flüssig	mm (Zoll)	15,88 (5/8)	15,88 (5/8)	15,88 (5/8)	15,88 (5/8)	19,05 (3/4)	
		Sauggas	mm (Zoll)	28,58 (1 1/8)	28,58 (1 1/8)	28,58 (1 1/8)	34,9 (1-3/8)	34,9 (1-3/8)	
		Heißgas	mm (Zoll)	22,2 (7/8)	22,2 (7/8)	28,58 (1 1/8)	28,58 (1 1/8)	28,58 (1 1/8)	
Rohrleitungslänge	Gesamt	Max	m	1000	1000	1000	1000	1000	
	ab 1. Abzweig ⁸	Max	m	40 (90)	40 (90)	40 (90)	40 (90)	40 (90)	
	Höhe AE-IE	Max	m	110	110	110	110	110	
	Höhe IE-IE	Max	m	40	40	40	40	40	
Kältemittel R410A	Werksfüllung ⁹ / t - CO ₂ -Äquivalent			16 / 33,44	16 / 33,44	16 / 33,44	17 / 37,53	17 / 37,53	
Spannungsversorgung	V / Ph / Hz			400 / 3 / 50	400 / 3 / 50	400 / 3 / 50	400 / 3 / 50	400 / 3 / 50	
Elektroleitung ¹⁰	Verbindungs- leitung	AE-IE	Anz. X mm ²	LIYCY 2 x 1,0	LIYCY 2 x 1,0	LIYCY 2 x 1,0	LIYCY 2 x 1,0	LIYCY 2 x 1,0	
Absicherung ¹⁰	träge	Max	A	50	50	50	63	63	
PREIS				ARUM180LTE5	ARUM200LTE5	ARUM220LTE5	ARUM240LTE5	ARUM260LTE5	
Multi V 5 Außeneinheit				€	31.700	34.800	36.100	38.500	42.500